

Perfect Panel Computers for

AUTOMATION

Innovative HMI Products

Intel® Apollo Lake processor, Fan-Less Design*,
LED Backlight Technology, Full Dimming 100%,
Low Power Consumption, Multi-Power*,
Superior Optical Bonding Option, Multi-
Touch Option*, EN60945 Tested,
Type Approved EU-RO-MR**

* = Check specifications for details

** = pending for 8.0, 13.3 and 15.6 inch

Our cost effective and high quality, all in one Panel computer, fulfil a wide range of requirements in manufacturing and process Automation.

Multi-touch user interfaces can be added easily to all available models. These models have a wide range of mounting options such as in a control cabinet or on a mounting arm.



SPECIFICATIONS

DISPLAY TECHNOLOGY & MECHANICAL



8.0"

8.0"

13.3"

15.6"

	Response Time & View Angle (typ)	Contrast Ratio (typ) & Light Intensity (typ)	Pixel Pitch (mm)	Active Area (mm)	Power Input & Options	Power Consumption (typ/max) & Inputs	Dimensions (WxHxD) (mm [inch] & Compass Safe Distance (cm [inch]))
8.0" HD 08T30 MMC	25ms (tr+tf) 85° (u/d/l/r)	650:1 600 cd/m ²	0.2208 (H) 0.2070 (V)	176.64 (H) 99.36 (V)	Single 12-24VDC Nominal	17W / 20W	228.00 [9.01"] x 156.60 [6.17"] x 65.80 [2.59"] Standard: 60.00 [23.62"] - Steering: 25.00 [9.84"]
8.0" HD 08T30 MMC-T	25ms (tr+tf) 85° (u/d/l/r)	650:1 600 cd/m ²	0.2208 (H) 0.2070 (V)	176.64 (H) 99.36 (V)	Single 12-24VDC Nominal	17W / 20W	236.00 [9.29"] x 166.00 [6.54"] x 62.70 [2.47"] Standard: 60.00 [23.62"] - Steering: 25.00 [9.84"]
13.3" HD 13T30 MMC	25ms (tr+tf) 85° (u/d/l/r)	600:1 600 cd/m ²	0.1529 (H) 0.1529 (V)	293.76 (H) 165.24 (V)	Single 12-24VDC Nominal	30W / 34W	355.00 [13.98"] x 248.50 [9.78"] x 69.00 [2.72"] Standard: 60.00 [23.62"] - Steering: 35.00 [13.78"]
15.6" HD 16T30 MMC	35ms (tr+tf) 85° (u/d/l/r)	1500:1 400 cd/m ²	0.17925 (H) 0.17925 (V)	344.16 (H) 193.59 (V)	Multi-Power 100-240V AC - 50/60Hz + 24VDC or Single 100-240V AC - 50/60Hz	44W / 57W	397.60 [15.65"] x 279.50 [11.00"] x 94.50 [3.72"] Standard: 60.00 [23.62"] - Steering: 35.00 [13.78"]
Additional Details	Native Resolution & Aspect Ratio: 8.0" = 800 x 480, 13.3" / 15.6" = 1920 x 1080 (FHD) - 16:9 Max Colors: 16.77M colors (24bit / RGB 8-bit) Operating / Storage Temperature / Humidity / IP Rating: -15°C to +55°C / -20°C to +60°C / Humidity up to 95% / IP66 front - IP20 rear (EN60529). IP22=option User Controls: Power On/Off, Brightness Control (-/+), Power LED, ECDIS LED (15.6" only), Buzzer, Light Sensor						



8.0" with HD IO-Board

Signal, I/O & Power Ports 8.0" / 13.3"	HD-IO Board: Signal, I/O & Power Ports 8.0" / 13.3"	Signal, I/O & Power Ports 15.6"
2 x USB2.0 (Type A), 2 x USB3.0 (Type A), 2 x GbLAN (RJ45), 1 x 2-pin Terminal Block 5.08	in addition to standard connectors: 2 x M12, NMEA2000 CAN, Isolated 4 x RS422/RS485, NMEA183 COM, Isolated 1 x 5-pin T. Block 3.81, Digital In+Out, Isolated 1 x RS-232/RS-485/RS-422, DB9M, non-isolated	2 x DisplayPort (DP), 2 x USB2.0 (Type A), 2 x GbLAN (RJ45), 1 x RS-232/422/485 (DB9M), AC: 1 x Std. IEC Inlet, if DC: 1 x 2-pin T.Block 5.08



13.3" with HD IO-Board

Factory Options for **8.0"** / **13.3"** - Note: Factory Default is with Projected Capacitive Touch Screen (Multitouch, USB interface), AG Coated Front Glass, Dust Covers and USB Cable Support Bracket
IP22 (EN60529) Model, HD IO-Board Expansion, Optical Bonding Technology, ATEX C1D2 and UL certification

Factory Options for **15.6"**
Projected Capacitive Touch Screen (Multitouch, USB, Pen, Glove support), Optical Bonding Technology, TPM2.0 (Trusted Platform Module),
1 x 1 x HT 00235 OPT-A1: 2W Amplified Audio out via DB9F, 1 x Diskbay with support for 2 x 2.5" or One HD USB module installed as:
1 x PCA100309-1: Dual Isolated RS-232, connector 2xDB9 or 1 x ZIA0001310-B: CAN isolated 2 channel or 2 x 4 channel or 1 x PCA100297-1: Isolated Digital IO module, 4 x OUT/4 x IN or 1 x PCA100298-1: LAN 10/100Mbps, 2 ports RJ45

Available Accessories (review datasheet for complete details)

For 8.0": External Fan & USB External Modules. **For 13.3"**: External Fan, Table / Ceiling Mount Bracket, UV Sun Cover & USB External Modules
For 15.6": Console Mount kit, Table / Ceiling Mount Bracket & USB External Modules

COMPUTER TECHNOLOGY

Supported Operating Systems (OS)	Default Processor / CPU	Default Memory / RAM Installed	Default Storage Device	System / Graphics Chipsets
Windows® 10 IoT Enterprise 2016 LTSB (64bit) (Product Distribution End Date November 2025)	8.0" / 13.3" : Intel® Atom® x5-E3930, 1.30GHz / 1.80GHz, 2M Cache 15.6" : Intel® Atom® x7-E3950, 1.60GHz / 2.00GHz, 2M Cache	2GB DDR3L, SO-DIMM, 1600MHz, Single Channel	32GB eMMC installed	Intel® SOC Intel® HD Graphics 500 / 505
Ethernet GbLAN	BIOS / BUZZER	Speaker / WatchDog Timer	Other Features	
Realtek Gigabit LAN 10/100/1000Mbps Intel Gigabit LAN 10/100/1000Mbps	AMI BIOS, supports ACPI Yes (according to EN60945)	None Yes (256 segments, 0, 1, 2...255 sec/min)	RTC (0.5s/day*), Battery Alarm, WakeOnLan, Fast Boot, AT mode, USB Boot, TPM2.0 (option for 15.6")	
Available Memory / RAM Configurations	Available Storage Device Configurations		Available OS Configurations	
2GB, 4GB, 8GB	240GB m.2 (internal addition)		Linux: Please contact us.	



15.6" with Modules